
Remove wheel caps.


Retension snow chains after driving for a short distance!
When driving with snow chains, do not exceed max. speed of 50 km/h!
On roads free of snow, drive with restraint for safety reasons and to protect chains.


Mercedes-Benz non-skid chains with gripping studs (up to 1982)

Tire size	Part no.	Code no.1)
175 R 14	000 583 66 16	07 325
185 R 14	000 583 68 16	17 328
195/70 R 14	000 583 89 16	16 327
205/70 R 14	000 583 81 16	16 329
215/70 R 14	000 583 88 16	16 331
185 R 15	000 303 80 10	




Tire size	Part no.	Code no.1)
175/70 R 14	201 583 00 16	46 320
175 R 14	123 583 00 16	46 325
185 R 14	107 583 00 16	46 328
195/70 R 14	107 563 00 10	
205/70 R 14	126 583 00 16	46 329
215/70 R 14	116 583 00 16	46 331
185 R 15	110 303 00 10	
205/65 R 15	107 583 01 16	46 384
		·





Mercedes-Benz non-skid chains without gripping studs RUD-matic system (starting 1983)

Tire size	HW-part no.	Code no.1)
175/70 R 14	758 0265	44 320
175 R 14	758 0266	44 325
185 R 14	758 0267	44 328
195/70 R 14		44 320





Part no./code no. ¹)
417-048
417-056
417-059
417-057
417-054
417-061

Milz ring chain

Tire size	Without gripping studs Y-grip pattern code no. ¹)	With gripping studs Y-super grip pattern code no.1)
175/70 R 14	60 or 20 060	
175 R 14	70 or 20 070	23 070
185 R 14 195/70 R 14	80 or 20 080	23 080
205/70 R 14	90 or 20 090	23 090
215/70 R 14	100 or 20 100	23 100
165 R 15	90 or 20 090	23 090
205/65 R 15	90 or 20 090	23 090








RUD-"non skid" (up to 1982)

Part no. ¹)	
07 125	
17 128	
16 127	
16 129	
16 131	



RUD-matic type "non-skid" (starting 1983)

Tire size	Part no. 1)
175/70 R 14	46 120
175 R 14	46 125
185 R 14 195/70 R 14	46 128
205/70 R 14	46 129
215/70 R 14	46 131
185 R 15	46 131
205/65 R 15	46 184

Code numbers or part numbers are each stamped-in at closing hook of tensioning chain or at outer (red) steel rope ring.



140-25707